

# DUVEPRO Polyester/Felt Tape



## Technical Data Sheet

**DuvePro is a soft polyester felt tape with permanent acrylic adhesive protected by a liner.**

### Features & Benefits:

Velcro™ compatible  
Very Flexible

### Technical Data

- ⇒ Backing: Soft polyester felt
- ⇒ Adhesive: Permanent acrylic
- ⇒ Color: Black
- ⇒ Thickness: 26.0 mils
- ⇒ Liner: 92 lb Poly stay flat
- ⇒ Loop tack: 35 oz. per inch
- ⇒ FMVSS302: Passed
- ⇒ Polyester Felt Max Intermittent Temperature: 325°F
- ⇒ Polyester Felt Max Continuous Temperature: 300°F
- ⇒ Adhesive Application Temperature: -20 to 200°F
- ⇒ *Storage: Must be stored upright on its cut edges. We recommend storage in moderate conditions(60°F to 70°F). It is advisable to store DuvePro in its original packing to maintain optimum performance characteristics.*

### Application:

DuvePro can be used to create an instant backdrop. DuvePro can also be used to repair and seam curtains. Blocks out light and “hot spots”. DuvePro can be used to cover lighting trusses or create a header on a display. DuvePro is Velcro™ compatible.

ISO 9001  
Certified



621 Route One South. North Brunswick, NJ 08902  
Toll Free #1-800-345-0234

*Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.*