

# PRO® 156

5 MIL 3" I.D. Core ADHESIVE  
TRANSFER TAPE



## Technical Data Sheet

**Pro® 156 is a 5 mil adhesive transfer tape  
on a kraft liner.**

### Features & Benefits:

Extremely high adhesion  
Good shear strength  
Excellent gap filling properties

### Technical Data

- ⇒ Liner: 60# 4 mil Moisture Stable Kraft Liner
- ⇒ Adhesive: 5 mil Acrylic
- ⇒ Thickness without liner: 5.0 mils
- ⇒ Tape Thickness with liner: 9.0 mils
- ⇒ Color: Clear
- ⇒ Adhesion to steel: 75 oz./in
- ⇒ Low temperature application: 10°F
- ⇒ Heat resistance: 250°F
- ⇒ Application Temperature Range: 70°F to 100°F
- ⇒ 3" ID Core
- ⇒ MIL-P-19834B, Amend I
- ⇒ Chemical Resistance: Medium
- ⇒ Not intended for direct UV Light.

### Application:

Pro® 156 can be used as a laminating adhesive for foam, fabrics, metal or plastic nameplates and is an excellent product for splicing of films, fabrics and foils. It is also suited for joining materials with irregular or textured surfaces.

ISO 9001  
Certified



621 Route One South. North Brunswick, NJ 08902  
Toll Free #1-800-345-0234  
sales@protapes.com

*Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.*