

PRO® 4000 Printed

Printable Paper Application Tape



Technical Data Sheet

Pro® 4000 Printed is a medium tack printable paper application tape for vinyl graphics used in sign making and surface protection.

Features & Benefits:

Easy to remove from most surfaces

Perforated for easy tear by hand

AVAILABLE IN TWO PRINT OPTIONS(SIZING & NUMBER OF SIGNS PER ROLL DIFFERENT ON EACH PRINT OPTION)

Option 1: 6"x10" signs printed with the phrase "PLEASE STAY 6 FEET APART" Printed Black 20 signs in each roll.

Option 2: 2"x6" signs printed with the phrase "CLEANED & SANITIZED" Printed Blue 100 signs in each roll.

Technical Data

- ⇒ Backing: White translucent latex saturated paper
- ⇒ Adhesive: Water based natural latex
- ⇒ Elongation: 2.4%
- ⇒ Total Thickness: 4.0 mils
- ⇒ Adhesion to Steel: 17 oz. per inch
- ⇒ Tensile Strength: 20 lbs. per inch



Application:

Pro® 4000 Printed is a medium tack paper tape used in a variety of applications to help support social distancing guidelines along with health & sanitization requirements. Product can be used in education, hospitality, and corporate settings to support clean and safe environments.

AVAILABLE IN TWO PRINT OPTIONS(SIZING & NUMBER OF SIGNS PER ROLL DIFFERENT ON EACH PRINT OPTION)

Option 1: 6"x10" signs printed with the phrase "PLEASE STAY 6 FEET APART" Printed Black 20 signs in each roll.

Option 2: 2"x6" signs printed with the phrase "CLEANED & SANITIZED" Printed Blue 100 signs in each roll.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902
Toll Free #1-800-345-0234

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.