

PRO[®] 500B D/C Cloth Tape



Technical Data Sheet

Pro[®] 500B is a double-coated cloth tape on a blue release liner.

Features & Benefits:

- High grade silicone coated polyethylene release liner facilitates easy unwind.
- Extremely aggressive adhesive.
- Designed for residue-free removal.
- Conformable and moisture resistant.
- Easy tear.
- Low VOC Content
- High tack.

Technical Data

- ⇒ Adhesive: Natural Rubber
- ⇒ Backing: Cloth
- ⇒ Thickness: 11.0 mils (ASTM D-1000)
- ⇒ Tensile strength: 20 lbs. per inch (ASTM D-1000)
- ⇒ Tack (Rolling Ball): 20 lbs. per inch (PSTC-6)
- ⇒ Adhesion to steel: 2 in., 5.1cm (PSTC-1)
- ⇒ Service Temperature: 40°F to 200°F
- ⇒ Adhesion to Steel: 40 oz. per inch
- ⇒ Specifications: Boeing BAC5034-4 Section 5.1.a(1)(a); BAC-5317 Rev F

Application:

Pro[®] 500B is a carpet hold-down tape designed especially for the convention industry. Pro[®] 500B is used for hanging, seaming and poly sheeting. Other general purpose uses for Pro[®] 500B are in construction and aircraft manufacturing.



621 Route One South. North Brunswick, NJ 08902
Toll Free #1-800-345-0234

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.