

PRO® 5110W

EHB (Extreme High Bond) Tape



Technical Data Sheet

Pro® 5110W EHB (Extreme High Bond) Tape is used in many indoor and outdoor applications.

Features & Benefits:

Modified acrylic adhesive bonds well to metals, glass, painted surfaces and medium/low surface energy plastics
Acrylic foam combines a high level of internal strength
45mil Thickness helps adhesion to irregular surfaces

Technical Data

- ⇒ Adhesive: Modified Acrylic
- ⇒ Thickness: 45.0 mils
- ⇒ Tensile strength: 86 lbs. per inch
- ⇒ Density: 52 lbs. per feet
- ⇒ 90°F Peel adhesion: 22 lbs. per inch
- ⇒ Release Liner: 5mil Red Polyethylene
- ⇒ Foam Color: White
- ⇒ UV Resistance: Excellent
- ⇒ Solvent Resistance: Excellent
- ⇒ Temperature Resistance: Long Term: 212°F, Short Term: 320°F

Application:

Pro® 5110W is used in many indoor and outdoor applications. EHB Tape often replaces spot welds, rivets, nails, liquid adhesives and other permanent fasteners.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902
Toll Free #1-800-345-0234
sales@protapes.com

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.