

# PRO® 822

## Heavy Duty Reverse Wound Floor Protection Film



### Technical Data Sheet

**Pro® 822 is a Heavy Duty Reverse Wound Floor Protection Film**

#### Features & Benefits:

Product is reverse wound and can be easily applied by hand or with an applicator

Product has a medium tack level

#### Technical Data

- ⇒ Backing: Polypropylene film
- ⇒ Adhesive: Water-based acrylic adhesive
- ⇒ Tensile strength: 11 lbs./inch
- ⇒ Adhesion to steal: 2.0-4.5 oz./inch
- ⇒ Elongation: 325%
- ⇒ Total Thickness: 3.0 mils
- ⇒ Tack level: Medium

#### Application:

Pro® 822 is a polyethylene film coated with an inert water-based acrylic adhesive. The product is reverse wound and can be easily applied by hand or with an applicator. This temporary floor protection film provides protection during painting, remodeling, relocations or other high traffic situations. The many variations in floor materials; wood, natural stone, ceramics, etc. and the finishing techniques for each, make it imperative that the user determines its suitability

ISO 9001  
Certified



621 Route One South. North Brunswick, NJ 08902  
Toll Free #1-800-345-0234

*Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminates.*