

PRO® 919

Heavy Duty Carton Sealing Tape



Technical Data Sheet

Pro® 919 is a heavy duty polypropylene film coated with a high tack adhesive.

Features & Benefits:

- Easy Unwind
- High strength polypropylene backing
- Excellent strength and high impact resistance
- High performance quick grab adhesive
- Water and abrasion resistant
- Excellent for use with recycled corrugate

Technical Data

- ⇒ Backing: 2.0 mils Biaxially Oriented Polypropylene Film
- ⇒ Adhesive: Synthetic Rubber Resin
- ⇒ Total Tape Thickness: 3.0 mils
- ⇒ Colors: Tan or Clear
- ⇒ Tensile strength: 35 lbs. per inch
- ⇒ Elongation: 140%
- ⇒ Adhesion to steel: 55 oz. per inch
- ⇒ Tan meets US military specification: PPP-T-60E Type III, Class 1
- ⇒ Clear is considered water resistant as per ASTM D5570 and also complies with the Federal Food, Drug and Cosmetic Act, CFR Title 21, Subpart B, Par. 175.105 (covers the use of pressure sensitive adhesives and tapes for 'indirect contact' food packaging, such as box sealing). CID A-A-1684B and ASTM D5486 Type III.

Application:

Pro® 919 is a heavy duty polypropylene film coated with high tack adhesive designed for automatic packaging and carton sealing equipment lines. Pro® 919 is specifically designed for heavy duty carton sealing applications. It is also used for smooth easy dispensing either manually or automatically.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902
Toll Free #1-800-345-0234
sales@protapes.com

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.