

# PRO<sup>®</sup> CHART TAPE

## Flatback Paper Tape



### Technical Data Sheet

**Pro<sup>®</sup> Chart Tape is a premium flatback paper**

#### **Features & Benefits:**

Repositionable, clean removal adhesive system that leaves no residue. Provides good tensile strength, as well as high edge tear resistance and easy unwind.

White is PH Neutral

Printable with pen or sharpie marker

Used for marking lines on charts, dry erase boards and maps

Available in 7 standard colors: White, Black, Green, Blue, Red, Yellow, and Orange

#### **Technical Data:**

- ⇒ Backing: Flatback Paper
- ⇒ Adhesive: Synthetic Rubber
- ⇒ Thickness: 5.8 mils
- ⇒ Tensile strength: 30 lbs. per inch
- ⇒ Adhesion to steel: 57 oz. per inch
- ⇒ Elongation: 2.5%
- ⇒ Temperature Range: 40°F to 150°F

#### **Application:**

Pro<sup>®</sup> Chart Tape is used for color coding, labeling and is printable with flexo inks, markers, pens, pencils. Pro<sup>®</sup> Chart Tape removes cleanly and safely from sound and lighting boards. Will not stain or ghost after removal. Pro<sup>®</sup> Chart Tape is used for marking lines on charts, dry erase boards and maps.

ISO 9001  
Certified



621 Route One South. North Brunswick, NJ 08902

Toll Free #1-800-345-0234

[sales@protapes.com](mailto:sales@protapes.com)

*Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.*