

# PRO<sup>®</sup> DUCT 120

## Industrial Grade Duct Tape



### Technical Data Sheet

**Pro<sup>®</sup> Duct 120 is an industrial grade duct tape used for a wide variety of applications.**

#### Features & Benefits:

- Waterproof Backing
- Highly Conformable
- Easy Unwind
- Aggressive Adhesive
- Indoor/Outdoor use
- Excellent high tack
- Competitively priced



#### Technical Data

- ⇒ Adhesive: Natural Rubber
- ⇒ Backing: Polyethylene coated cloth
- ⇒ Thickness: 10.0 mils
- ⇒ Tensile strength: 27 lbs. per inch
- ⇒ Elongation: 17%
- ⇒ Adhesion to steel: 55 oz./in
- ⇒ Colors: Silver, Black, Tan, Brown, Red, Olive Drab, White, Blue, Green, Orange, Yellow, Burgundy, Purple
- ⇒ Service Temperature Range: 50°F to 200°F
- ⇒ Specification: Tested in accordance with UL 723

#### Application:

Pro<sup>®</sup> Duct 120 is used for carton sealing, book binding, splicing, masking, seat repair, securing or holding and general purpose bundling. Pro<sup>®</sup> Duct 120 can be used as a moisture barrier. Pro<sup>®</sup> Duct 120 typical applications include HVAC, industrial, commercial, utilities, trucking and automotive.

ISO 9001  
Certified



621 Route One South. North Brunswick, NJ 08902  
Toll Free #1-800-345-0234

*Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.*