

PRO GAFF® PRINTED Industrial Grade Floor Marking Tape for Social Distancing



Technical Data Sheet

Pro Gaff® Printed version for industrial grade floor marking tape for social distancing.

Features & Benefits:

- High strength, high performance adhesive system
- Highly conformable to irregular surfaces
- Weather resistant
- High thread count
- Abrasion resistant
- Clean removability from most surfaces
- FL Colors are UV light friendly for high visibility
- Premium gaffers tape
- Smooth, controlled unwind
- Hand Tearable

Available in two convenient formats:

- **6"x10" pieces/sheets/signs on a liner "PLEASE STAY 6 FEET APART"**
Colors available: White printed red ink, White printed black ink, FL Pink printed black Ink, FL Yellow printed black ink
- **Roll Form 3" wide Pro Gaff printed black on a liner and perforated for easy tear.**
3 different prints available: "X PLEASE STAND HERE X", "6FT STAY 6FT SAFE 6FT", "<- SOCIAL DISTANCE - 6 FEET->" in six color options: FL Blue, FL Pink, FL Orange, FL Green, FL Yellow, and White.
***FL Yellow is stock**

Technical Data

- ⇒ Backing: Cotton Cloth
- ⇒ Adhesive: Synthetic rubber based
- ⇒ Tensile strength: 50 lbs. per inch
- ⇒ Elongation: 4%
- ⇒ Total Thickness: 11 mils
- ⇒ Adhesion to steel: 75 oz./in



Application:

Pro Gaff® Industrial Grade Floor Marking Tape for Social Distancing is available in two variety's: 6"x10" pieces/sheets/signs on a liner printed "PLEASE STAY 6 FEET APART" and also in roll form 3 inch wide by 3 foot long strips printed black ink on a liner and perforated for easy tear.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902
Toll Free #1-800-345-0234
sales@protapes.com

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminates.