

PRO[®] SEAL 300 Carton Sealing Tape



Technical Data Sheet

Pro[®] Seal 300 is a polypropylene general purpose carton sealing tape.

Features & Benefits:

Outstanding holding power

Water and abrasion resistant

High performance quick-grab adhesive is excellent for use on a wide variety of surfaces.

Easily applied, by hand or automatically

Available in clear that assures maximum readability of carton markings

Technical Data

- ⇒ Adhesive: Synthetic Rubber/Hot Melt
- ⇒ Tensile strength: 19 lbs. per inch
- ⇒ Elongation at break: 110%
- ⇒ Total Thickness: 1.6 mils
- ⇒ Adhesion to steel: 26 oz. per inch
- ⇒ Service temperature: 30° F– 140° F
- ⇒ Application temperature: 54° F–110° F
- ⇒ Colors: Tan and clear
- ⇒ Specifications: CID A-A-1684C, ROHS Compliant, ASTM D 1974-92

Application:

Pro[®] Seal 300 is used for all general purpose carton sealing applications. Pro Seal 300 is designed for smooth, easy dispensing.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902

Toll Free #1-800-345-0234

sales@protapes.com

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications.