

# PRO<sup>®</sup> SEAL 300AC Carton Sealing Tape



## Technical Data Sheet

**Pro<sup>®</sup> Seal 300AC is a polypropylene general purpose carton sealing tape.**

### **Features & Benefits:**

- Outstanding holding power
- Water and abrasion resistant
- High performance quick-grab adhesive is excellent for use on a wide variety of surfaces.
- Easily applied, by hand or automatically
- Available in clear that assures maximum readability of carton markings
- Water based acrylic adhesive is non-yellowing and weather resistant
- Works well in cold temperatures

### **Technical Data**

- ⇒ Backing: Biaxially Oriented Polypropylene Film
- ⇒ Adhesive: Water Based Acrylic
- ⇒ Tensile strength: 18 lbs. per inch
- ⇒ Elongation: 100%
- ⇒ Total Thickness: 2.0 mils
- ⇒ Adhesion to steel: 22 oz. per inch
- ⇒ Application Temperature: 32°F to 140°F
- ⇒ Colors: White, Black, Yellow, Orange, Red, Blue, Green, Pink & Purple
- ⇒ Approved for indirect food contact

### **Application:**

Pro<sup>®</sup> Seal 300AC is used for all general purpose carton sealing applications. Pro Seal<sup>®</sup> 300AC is designed for smooth, easy dispensing.

ISO 9001 Certified



621 Route One South. North Brunswick, NJ 08902

Toll Free #1-800-345-0234

*Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.*