

PRO® 248

Double Sided Butyl Tape



Technical Data Sheet

Pro® 248 is a double sided tape with polyethylene net carrier, both sides coated with waterproofing butyl adhesive.

Features & Benefits:

Superior durability
Cold and heat resistance

Technical Data

- ⇒ Adhesive: Butyl Rubber
- ⇒ Carrier: PE Net
- ⇒ Total Thickness: 20.0 mils
- ⇒ Color: Black with black adhesive
- ⇒ Tack: 40 (ball no.)
- ⇒ Holding power: 10 minutes to drop
- ⇒ Adhesion to steel: 87 oz. per inch
- ⇒ Tensile Strength: 9 lbs. per inch
- ⇒ Maximum Temperature: 200°F

Application:

Pro® 248 is used for waterproofing of residential houses and noise insulation applications because of its superior durability and excellent cold and heat resistance. Pro® 248 is ideal for temporary fixing, joint sealing of building materials, fixing of floors, residential air sealing and damp proofing, fixing sheet metal and insulation and vibration control. Pro® 248 is an excellent product to be used when installing metal roofing.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902
Toll Free #1-800-345-0234
sales@protapes.com

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications.