

# PRO® 965

## Double Coated Tape



### Technical Data Sheet

**Pro® 965 is a double coated adhesive tape consisting of transparent polyester film with a pink PP release liner.**

#### **Features & Benefits:**

- Resistant to plasticizers
- Offers a secure bond even at elevated temperatures
- Self-adhesive mounting capabilities

#### **Technical Data**

- ⇒ Total Tape Thickness: 7.87 mils
- ⇒ Backing: PET Film
- ⇒ Adhesive: Tackified Acrylic
- ⇒ Liner: 3.0 mil MOPP Film, Pink
- ⇒ Color: Transparent
- ⇒ Tensile strength: 2 lbs. per inch
- ⇒ Elongation: 55%
- ⇒ Adhesion to steel: 96 oz./in
- ⇒ Short Term Temperature Resistance: 266°F
- ⇒ Long Term Temperature Resistance: 176°F

#### **Application:**

Pro® 965 has an adhesive system developed to be resistant to plasticizers and offers a secure bond even at elevated temperatures. Pro® 965 is used for mounting of decorative profiles and molding and plastic parts in the automotive industry and self-adhesive mounting of rubber/EPDM profiles.

ISO 9001  
Certified



621 Route One South. North Brunswick, NJ 08902  
Toll Free #1-800-345-0234

*Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.*