

PRO® Carpet Safe Tape

Double Coated Carpet Tape



Technical Data Sheet

Pro® Carpet Safe Tape is a double coated carpet hold down application tape.

Features & Benefits:

Easy to use and remove cleanly
Excellent for temporary holding

Technical Data:

- ⇒ Adhesive: Synthetic rubber-based/aggressive natural rubber
- ⇒ Liner: White natural kraft paper
- ⇒ Liner thickness: 3.94 mils
- ⇒ Total thickness without liner: 22.52 mils
- ⇒ Total thickness with liner: 26.46
- ⇒ Tensile strength (open side): 21 lbs./inch
- ⇒ Tensile strength (liner side): 6.2 lbs./inch
- ⇒ Adhesion to steel (open side): 32 oz./inch
- ⇒ Adhesion to steel (liner side): 8.5 oz./inch
- ⇒ Elongation (open side): 9%
- ⇒ Elongation (liner side): 12%
- ⇒ Colors: Blue

Application:

Pro® Carpet Safe Tape is a quality application tape used for temporary carpet hold down. Product is an excellent resource when setting up carpets for showrooms, tradeshow, and general events.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902
Toll Free #1-800-345-0234
sales@protapes.com

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants. Adhesives are compliant with FDA regulations for indirect food contact—CFR 175.105