

PRO® 929

Heavy Duty Polyester Carton Sealing



Technical Data Sheet

Pro® 929 is a superior performance polyester packaging and label protection tape.

Features & Benefits:

- Polyester backing
- Pressure sensitive hot melt rubber-resin adhesive
- Adheres instantly to most surfaces including cartons containing high levels of recycled content
- Strong abrasion resistant backing with high edge tear and split resistance
- High performance ensures reliable closures

Technical Data

- ⇒ Backing: 2.0 mil Biaxially Oriented Polyester Film
- ⇒ Adhesive: Pressure sensitive hot melt rubber-resin
- ⇒ Colors: Clear, Tan
- ⇒ Total Tape Thickness: 3.43 mil
- ⇒ Tensile strength: 67 lbs. per inch (MD) 69 lbs. per inch (CD)
- ⇒ Elongation: 130%
- ⇒ Adhesion to steel: 78 oz./in
- ⇒ Storage Temperature: 40°F to 80°F, 40-50% Relative Humidity
- ⇒ Specification: Meets Fed. Spec. PPP-T-60E, Amend. 2, Type III, Class 2 (clear), CID A-A-1830B (clear), ASTM D5486 Type 1 & 2, CID A-A 1684C

Application:

Pro® 929 is used for box sealing, splicing, re-cooperage and other demanding packaging applications. This product has a strong abrasion resistant backing and the most consistent pressure sensitive hot melt adhesive system available. This time proven construction assures high performance in a wide range of environments and applications.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902
Toll Free #1-800-345-0234
sales@protapes.com

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.