

PRO® DRAFTING Low Tack Masking



Technical Data Sheet

Pro® Drafting is a low tack masking tape with a specially formulated adhesive system, designed for drafting and stationery trades.

Features & Benefits:

- Minimizes residues
- Resists water solvents and oil
- Excellent shelf-life
- Specially designed for stationary trades
- pH Neutral

Technical Data

- ⇒ Backing: White translucent latex saturated paper
- ⇒ Adhesive: Water based natural latex
- ⇒ Thickness: 4.0 mils
- ⇒ Tensile strength: 20lbs. per inch
- ⇒ Color: Natural
- ⇒ Adhesion to Steel: 17 oz./in
- ⇒ Elongation: 2.4%

Application:

Pro® Drafting Tape minimizes residue and resists water solvents and oil and has excellent shelf-life. Not designed or guaranteed for exacting industrial masking spray, painting or oven baking applications.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902
Toll Free #1-800-345-0234
sales@protapes.com

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.