



# PRO® FLOCKING TAPE

## Anti-squeak Tape

### Technical Data Sheet

**Pro® Flocking Tape is an anti-squeak tape coated  
with an aggressive acrylic adhesive.**

#### **Features & Benefits:**

- Very aggressive acrylic adhesive
- Low fogging qualities
- Thick transfer tape
- Natural poly-coated moisture stable liner
- Used in anti-squeak applications
- High adhesion to low surface energy plastics
- High initial tack
- Strong, abrasion resistant poly-cotton flock

#### **Technical Data**

- ⇒ Adhesive: 1.0-1.1-mils of a general purpose permanent acrylic based adhesive.
- ⇒ Carrier: Flock Fiber Solution Dyed 100% Acrylic
- ⇒ Film: 3.5-mil General Purpose flexible black vinyl.
- ⇒ Liner: 4.7-mil one-side clay coated semi bleached release liner.
- ⇒ Total thickness: 9.30 mils
- ⇒ Adhesion:
  - Stainless Steel: 60 oz./in
  - Acrylic: 70 oz./in
  - Glass: 61 oz./in
  - Polypropylene: 15 oz./in
- ⇒ Expected Shear 25 hours
- ⇒ Service Temperature Range: -40°F to 176°F
- ⇒ Minimum Application Temperature: 50°F

#### **Application:**

Pro® Flocking Tape is designed for anti-squeak applications requiring high adhesion to low surface energy materials. Pro Flocking Tape is also recommended for use where low fogging is required.

ISO 9001  
Certified



621 Route One South. North Brunswick, NJ 08902

Toll Free #1-800-345-0234

sales@protapes.com

*Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications.*