

PRO® NET 10 Micro Scrim Tape



Technical Data Sheet

Pro® Net 10 is a micro scrim reinforced 3.2 mil thick acrylic adhesive transfer tape.

Features & Benefits:

- The conformability of an unsupported transfer tape that offers process ability of a double-coated tape
- Bonds to a wide variety of materials
- High peel and tack
- Aggressive adhesive with excellent quick stick
- Low VOC and odor
- No primers needed to promote adhesion

Technical Data

- ⇒ Adhesive: Acrylic
- ⇒ Adhesive Thickness: 3.2 mils
- ⇒ Liner: 74# Silicone Release Liner
- ⇒ Liner Thickness: 4.1 mils
- ⇒ Total Thickness (INCLUDING LINER): 7.3 mils
- ⇒ Adhesion to steel: 48 oz. per inch
 - Adhesion to other surfaces:
 - ABS: 50 oz. per inch
 - Polypropylene: 44 oz. per inch
- ⇒ Service Temperature: -40°F to 200°F
- ⇒ Storage Temperature: 70°F (21°C), 50% relative humidity

Application:

Pro® Net 10 is specifically designed for difficult bonding applications. This product has excellent quick stick for permanent bond applications on plastics, metals, nonwovens, felts, foams, including polyurethane, polyether, polyester, neoprene, polyethylene and EPDM.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902
Toll Free #1-800-345-0234

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.