

P- 665

General Purpose  
Vinyl Coated Cloth Tape

# Shurtape®

## TECHNICAL DATA

### TYPICAL APPLICATIONS

- > Gaffer's tape
- > Holding wiring, lighting and props
- > Color coding

### ADVANTAGES AND BENEFITS

- > High adhesion and tack
- > Clean removal
- > Conformable
- > Hand tearable
- > Wide variety of colors

### CONSTRUCTION

Overall Grade/Function: General Purpose Gaffer's Grade

Backing: Vinyl coated cloth

Adhesive: Synthetic rubber

### COLOR(S)



### STANDARD WIDTH(S)

3/4 in   24mm   48mm   72mm

### STANDARD LENGTH(S)

55 yd   55m

Contact your Shurtape sales representative for other available sizes.

### PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	48 lbs/in width	84.1 N/10 mm
Adhesion to Stainless Steel	80 oz/in width	8.76 N/10 mm
Thickness	11.5 mils	0.29 mm
Application Temperature	45 F to 200 F	7 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

### APPLICABLE STANDARDS

ASTM-D 5486M-06, Type IV; PPP-T-60E, Type IV, Class I; CID A-A-1586A

### STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

"Shurtape" is a registered trademark of Shurtape Technologies, LLC

Form# TDS-P-665- 1/26/2012