February 2025

PRO® 410 ATG

Double-coated ATG Tissue Bonding Tape (7.8 mils)

PRO TAPES
A Shurtape Technologies, LLC Company

Technical Data Sheet

Pro® 410 is a double coated non-woven tape coated on both sides with an aggressive acrylic pressure sensitive adhesive.

Features & Benefits:

Excellent adhesion to a wide variety of surfaces
Excellent resistance to:
Oils, some plasticizers, ultraviolet light, and can withstand higher temperatures than a rubber based adhesive
Acid-free

Technical Data

- ⇒ Backing: Tissue
- ⇒ Adhesive: Solvent based acrylic
- ⇒ Liner thickness: 3.5 mils
- ⇒ Thickness without liner: 4.33 mils
- ⇒ Total thickness with liner: 7.83 mils
- ⇒ Elongation: 3.50%
- ⇒ Initial Tack: 20cm (3 in., 11mm steel ball)
- ⇒ Adhesion to steel: 89 oz./in
- ⇒ Application Temperature: 50°F to 104°F
- ⇒ Service Temperature: -4°F to 212°F
- ⇒ Colors: Transparent with white liner
- ⇒ pH Level: 7 (Acid-free)
- ⇒ 1” ID Plastic Core

Application:

Pro® 410 ATG is used for bonding and laminating to a wide variety of cloths, vinyl's, corks, paper, rigid and flexible plastics. Pro® 410 ATG can be used for framing and mounting displays, such as signs, covers, posters, and nameplates. 1" ID Plastic Core. Compatible for use with our Pro ATG HD Dispenser.

ISO 9001 Certified

PERRY JOHNSON REGISTRARS, INC. ANAB ACCREDITED

621 Route One South. North Brunswick, NJ 08902
Toll Free #1-800-345-0234

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications.