

PRO® Dual Tack Floor Secure Tape

Double Coated Carpet Tape



A Shurtape Technologies, LLC Company

Technical Data Sheet

Pro® Dual Tack Floor Secure Tape is a double coated carpet hold down application tape.

Features & Benefits:

Easy to use and remove cleanly
Excellent for temporary holding
Strong adhesion

Technical Data

- ⇒ Adhesive: Synthetic rubber-based/aggressive natural rubber
- ⇒ Liner: White natural kraft paper
- ⇒ Liner thickness: 3.94 mils
- ⇒ Total thickness without liner: 20.52 mils
- ⇒ Total thickness with liner: 26.46
- ⇒ Tensile strength (open side): 21 lbs./inch
- ⇒ Tensile strength (liner side): 6.2 lbs./inch
- ⇒ Adhesion to steel (open side): 32 oz./inch
- ⇒ Adhesion to steel (liner side): 8.5 oz./inch
- ⇒ Elongation (open side): 9%
- ⇒ Elongation (liner side): 12%
- ⇒ Colors: Blue

Application:

Pro® Dual Tack Floor Secure Tape is perfect for stages or film sets when creating specific flooring in scenes or providing a suitable surface for performers and equipment. Other applications included events like tradeshow, exhibitions, showrooms and weddings.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902
Toll Free #1-800-345-0234

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications.